

# Product Data Sheet



**Panache**  
PAINT

## Panache Polyglo WB

No	JP08
Date	07/21

Panache products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.

### DESCRIPTION

Panache Supreme Polyglo WB is a non-drip multi-purpose water-based enamel paint with a satin sheen finish. Ideal for kitchens and bathroom walls, ceilings, trim, window and door frames, gutters, and downpipes.

### PRODUCT USES

- New and previously painted surfaces made from Cement Plaster, Concrete, Brickwork & Gypsum Plaster.
- Primed Asbestos/Fibre Cement Fascias & Ceiling Boards.
- Primed Steel & Wooden Surfaces.
- Ideal for Interior & Exterior Surfaces.

### PRODUCT BENEFITS

- Non-Yellowing
- Heat & Steam Resistant
- Quick Drying
- Washable
- 10 Year Guarantee

### SURFACE PREPARATION

**New Surfaces:** Surface/s must be thoroughly clean, dry and in sound condition before painting.

**Concrete/Cement Plaster:** Apply one coat of Panache SB Plaster Primer and wait 16 - 18 hours, then apply two coats of Panache Polyglo WB with correct drying time between coats.

**Asbestos/Fibre Cement:** Apply one coat of Panache SB Plaster Primer and wait 16 - 18 hours, then apply two coats of Panache Polyglo WB with correct drying time between coats.

**Iron & Steel:** Apply one coat of Panache Anti-Corrosive Primer and wait 4-6 hours, followed by one coat of Panache Universal Undercoat and wait 16 - 18 hours, then apply two coats of Panache Polyglo WB with correct drying time between coats.

**Timber/Wood:** Apply one coat of Panache Wood Primer and wait 16 - 18 hours, followed by one coat of Panache Universal Undercoat, and wait 16 - 18 hours, then apply two coats of Panache Polyglo WB with correct drying time between coats.

**Gypsum Plaster (Rhinolite/Rhinoglide):** Apply one coat of Panache SB Plaster and wait 16 - 18 hours, followed by two coats of Panache Polyglo WB with correct drying time between coats.

**PVC Gutters and Downpipes:** Apply 2 coat of Panache Multi-Purpose Primer, wait 4-6 hours between coats, then apply two coats of Panache Polyglo WB with correct drying time between coats.

### PREVIOUSLY PAINTED SURFACES

Thoroughly clean and prepare surface by removing all dirt, grease, grime and flaking paint before painting. Powdery surfaces must be treated with one coat of Panache Bonding Liquid and wait 16 hours, prior to applying two coats of Panache Polyglo WB with correct drying time between coats. Enamel based surfaces must be cleaned and prepared correctly. Sand lightly and apply one coat of Panache Universal Undercoat and wait 16 - 18 hours, followed by two coats of Panache Polyglo WB with correct drying time between coats.

## APPLICATION

Stir the contents thoroughly before use. This product should be applied without thinning. For colour consistency, ensure that batch numbers are the same on all cans. Apply this product with a paintbrush or (furpile / lambswool) paint roller or airless spray and allow 4-6 hours drying time between coats. Allow paint to cure (hard dry) for 7 days before attempting to clean the surface. Do not apply when rain is imminent. Clean tools (brushes & rollers) with Water immediately after use.

## COLOUR RANGE

Available in White, Black and 3 Tint Bases.

## PACKAGING:

Packaging: 1L & 5L

## SPREADING RATE

This product will cover approximately 8-10m<sup>2</sup> /litre, depending on surface porosity.

## TECHNICAL DATA

Type	Pure Acrylic
Finish	Satin Sheen
Drying Time @ 25°C	Touch Dry: 1 - 2 Hour Hard Dry: 4 - 6 Hours
Re-coating Time	4 - 6 Hours
Viscosity	95-110 Krebs units
Specific Gravity	-/+ 1.20 kg / Litre
Storage	Dry and Cool area

## PRECAUTIONS

- Do not apply if rain is imminent.
- Apply at an ambient temperature of 5 to 35°C.
- Keep out of reach of children.
- Wash hands with Water immediately after use.
- Skin or Eye contact: clean with fresh water and consult a physician if necessary.
- Do not paint before 9:00 and after 15:30.

## TOOL CHECKLIST

Paintbrush & Paint Roller Tray set; Plastic Drop Sheet; Mutton Cloth; Sandpaper; Masking Tape; Crack Filler; Paint Scraper; Stepladder.

## QUALITY GUARANTEE

This product is quality controlled and packed to the highest standard. Medal and Jack's Paint accepts no responsibility, nor accountability for either workmanship in surface preparation or the application of our products.

The information given in this Product Data Sheet is based on controlled laboratory tests and many years of experience. It is given in good faith, but no guarantee of any performance characteristic is given or implied. Jacks Paint cannot be held liable for consequential damage of whatsoever nature that may arise from the use of Panache products. Paint technology is continuously being developed and Jacks Paint reserves the right to update product specifications without prior notice. Contact Jacks Paint for further details on 0860 522 577.

