

Product Data Sheet



Panache
PAINT

Panache Multi-Purpose Primer

No	JP12
Date	07/21

Panache products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.

DESCRIPTION

Panache Supreme Multi-Purpose Primer for all smooth surfaces with excellent adhesion properties. Ideal for surfaces such as Melamine, galvanized iron, wood, glass and certain plastics.

PRODUCT USES

- Primed Steel & Galvanised Iron and Aluminium Surfaces.
- Ideal for Interior & Exterior Surfaces.

PRODUCT BENEFITS

- Excellent adhesion
- Rust inhibitor
- Lead Free
- Quality Guaranteed

SURFACE PREPARATION

New Surfaces: Surface/s must be thoroughly clean, dry and in sound condition before painting.

Iron & Steel: Apply one coat of Panache Multi-Purpose Primer and wait 4-6 hours, followed by one coat of Panache Universal Undercoat and wait 16 - 18 hours, then apply two coats of your desired Panache topcoat with correct drying time between coats.

Timber/Wood: Apply one coat of Panache Wood Primer or Panache Multi-Purpose Primer and wait 16 - 18 hours, followed by one coat of Panache Universal Undercoat, and wait 16 hours, then apply two coats of Panache Polyglo WB with correct drying time between coats.

PVC Gutters and Downpipes: Apply 2 coats of Panache Multi-Purpose, wait 4-6 hours between coats, then apply two coats of Panache Vinyl Silk with correct drying time between coats.

PREVIOUSLY PAINTED SURFACES:

Thoroughly clean and prepare surface by removing all dirt, grease, grime and flaking paint before painting. Rinse off well with water and allow it to dry quickly to avoid surface from rusting further. Apply one coat of Panache Multi-Purpose Primer and wait 4-6 hours, followed by two coats of your desired Panache topcoat with correct drying time between coats. Powdery surfaces must be treated with one coat of Panache Bonding Liquid and wait 16 - 18 hours, prior to applying two coats of your desired Panache Topcoat with correct drying time between coats.

NB: Failure to remove all red rusting may result in premature rust penetration through the applied paint system.

APPLICATION

Stir the contents thoroughly before use. This product should be applied without thinning. Apply this product with a paintbrush or (furpile / lambswool) paint roller and allow 4-6 hours drying time between coats. Ensure that the primer is overcoated within 72 hours of final coating. Do not apply when rain is imminent. Clean tools (brushes & rollers) with Water immediately after use.

NOTE 1: Do not apply the primer to damp or wet surfaces.

COLOUR RANGE

Available in White

PACKAGING:

Packaging: 1L & 5L

SPREADING RATE

This product will cover approximately 7-9m² /litre, depending on surface porosity.

TECHNICAL DATA

Type	Modified Hybrid Acrylic
Finish	Matt
Drying Time @ 25°C	Touch Dry: 1 - 2 Hour Hard Dry: 4 - 6 Hours
Re-coating Time	4 - 6 Hours
Viscosity	100-120 Krebs units
Specific Gravity	-/+ 1.23 kg / Litre
Storage	Dry and Cool area

PRECAUTIONS

Do not apply if rain is imminent.

Apply at an ambient temperature of 5 to 35°C.

Keep out of reach of children.

Wash hands with Water immediately after use.

Skin or Eye contact: clean with fresh water and consult a physician if necessary.

Do not paint before 9:00 and after 15:30.

TOOL CHECKLIST

Paintbrush & Paint Roller Tray Set; Plastic Drop Sheet; Mutton Cloth; Sandpaper; Masking Tape; Crack Filler; Paint Scraper; Stepladder.

QUALITY GUARANTEE

This product is quality controlled and packed to the highest standard.

Medal and Jack's Paint accepts no responsibility, nor accountability for either workmanship in surface preparation or the application of our products.

The information given in this Product Data Sheet is based on controlled laboratory tests and many years of experience. It is given in good faith, but no guarantee of any performance characteristic is given or implied. Jacks Paint cannot be held liable for consequential damage of whatsoever nature that may arise from the use of Panache products. Paint technology is continuously being developed and Jacks Paint reserves the right to update product specifications without prior notice. Contact Jacks Paint for further details on 0860 522 577.

