

Product Data Sheet



Panache
PAINT

Panache Artisan Trade Classic Sheen Acrylic

No	JP24
Date	07/21

Panache Artisan products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.

DESCRIPTION

Panache Artisan Trade Sheen Acrylic is an economical quality paint with a fine-smooth finish, which has been developed to protect and beautify all interior and exterior surfaces. This product is washable with good dirt resistance. It can be applied to a variety of surfaces where a durable low sheen finish is required.

PRODUCT USES

- New and previously painted surfaces made from Cement Plaster, Concrete, Brickwork & Gypsum Plaster.
- Asbestos/Fibre Cement Fascias & Ceiling Boards.
- Primed Metal & Wooden Surfaces.
- Ideal for Interior & Exterior Walls.

PRODUCT BENEFITS

- Good Dirt Resistance
- Washable
- Excellent Hiding Power
- Quality Guaranteed
- Fast drying

SURFACE PREPARATION

New Surfaces: Surface/s must be thoroughly clean, dry and in sound condition before painting.

Concrete/Cement Plaster: Apply one coat of Artisan Solvent Based Plaster Primer and wait 16-18 hours, then apply two coats of Artisan Trade Classic Sheen Acrylic PVA with correct drying time between coats.

Asbestos/Fibre Cement: Apply one coat of Artisan Solvent Based Plaster Primer and wait 16-18 hours, then apply two coats of Artisan Trade Classic Sheen Acrylic PVA with correct drying time between coats.

Iron & Steel: Apply one coat of Panache Anti-Corrosive Primer and wait 4-6 hours, followed by one coat of Artisan Universal Undercoat and wait 16-18 hours, then apply two coats of Artisan Trade Classic Sheen Acrylic PVA with correct drying time between coats.

Timber/Wood: Apply one coat of Panache Wood Primer-White and wait 16-18 hours, followed by one coat of Artisan Universal Undercoat and wait 16-18 hours, then apply two coats of Artisan Trade Classic Sheen Acrylic PVA with correct drying time between coats.

Gypsum Plaster (Rhinolite/Rhinoglide): Apply one coat of Artisan Plaster Primer and wait 16-18 hours, followed by two coats of Artisan Trade Classic Sheen Acrylic PVA with correct drying time between coats.

PREVIOUSLY PAINTED SURFACES

Thoroughly clean and prepare surface by removing all dirt, grease, grime and flaking paint before painting. Powdery surfaces must be treated with one coat of Panache Bonding Liquid and wait 16-18 hours, prior to applying two coats of Artisan Trade Classic Sheen Acrylic PVA with correct drying time between coats. Enamel based surfaces must be cleaned and prepared correctly. Sand lightly and apply one coat of Artisan Universal Undercoat and wait 16-18 hours, followed by two coats of Artisan Trade Classic Sheen Acrylic PVA with correct drying time between coats.

APPLICATION

Stir the contents thoroughly before use. This product should be applied without thinning. For colour consistency, ensure that batch numbers are the same on all cans. Apply this product with a paintbrush or (furpile / lambswool) paint roller and allow 4-6 hours drying time between coats. Allow paint to cure (hard dry) for 7 days before attempting to clean the surface. Do not apply when rain is imminent. Clean tools (brushes & rollers) with Water immediately after use.

COLOUR RANGE

Available in white. (Pastel colours can be tinted using white paint)

PACKAGING:

Packaging: 5L & 20L

SPREADING RATE

This product will cover approximately 6-8m² /litre, depending on surface porosity.

TECHNICAL DATA

Type	Acrylic
Finish	Low Sheen
Drying Time @ 25°C	Touch Dry: 1-2 Hour Hard Dry: 4-6 Hours
Re-coating Time	4-6 Hours
Viscosity	95-108 Krebs units
Specific Gravity	1.42 kg / Litre
Storage	Dry and Cool area

PRECAUTIONS

Do not apply if rain is imminent.

Apply at an ambient temperature of 5 to 35°C.

Keep out of reach of children.

Wash hands with Water immediately after use.

Skin or Eye contact: clean with fresh water and consult a physician if necessary.

TOOL CHECKLIST

Paintbrush & Paint Roller Tray set; Plastic Drop Sheet; Mutton Cloth; Sandpaper; Masking Tape; Crack filler; Paint Scraper; Stepladder.

QUALITY GUARANTEE

This product is quality controlled and packed to the highest standard.

Medal and Jack's Paint accepts no responsibility, nor accountability for either workmanship in surface preparation or the application of our products.

The information given in this Product Data Sheet is based on controlled laboratory tests and many years of experience. It is given in good faith, but no guarantee of any performance characteristic is given or implied. Jacks Paint cannot be held liable for consequential damage of whatsoever nature that may arise from the use of Panache products. Paint technology is continuously being developed and Jacks Paint reserves the right to update product specifications without prior notice. Contact Jacks Paint for further details on 0860 522 577.

