

# Product Data Sheet



**Panache**  
PAINT

## Panache Artisan Trade Universal Undercoat

No	JP29
Date	07/21

Panache products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.

### DESCRIPTION

Panache Artisan Trade Universal Undercoat is a versatile product, which is primarily used as an intermediate coat between the primer and final coat of paint. This product is an ideal base coat for enamel-based paints, or transforming an enamel painted surface to an Acrylic PVA.

### PRODUCT USES

- Primed new and previously painted surfaces made from Cement Plaster, Concrete, Brickwork & Gypsum Plaster.
- Primed Asbestos/Fibre Cement Fascias & Ceiling Boards.
- Primed Steel & Wooden Surfaces.
- Ideal for Interior & Exterior Surfaces.

### PRODUCT BENEFITS

- General Purpose Undercoat
- Good Adhesion Properties
- Excellent Hiding Power
- Quality Guaranteed
- Matt Finish

### SURFACE PREPARATION

**New Surfaces:** Surface/s must be thoroughly clean, dry and in sound condition before painting.

**Concrete/Cement Plaster:** Apply one coat of Panache SB Plaster Primer and wait 16-18 hours, followed by one coat of Artisan Trade Universal Undercoat, and wait 16-18 hours then apply two coats of your desired Artisan Trade Topcoat with correct drying time between coats.

**Asbestos/Fibre Cement:** Apply one coat of Panache SB Plaster Primer and wait 16-18 hours, followed by one coat of Artisan Trade Universal Undercoat, and wait 16-18 hours, then apply two coats of your desired Artisan Trade Topcoat with correct drying time between coats.

**Iron & Steel:** Apply one coat of Panache Anti-Corrosive Primer and wait 4-6 hours, followed by one coat of Artisan Trade Universal Undercoat and wait 16-18 hours, then apply two coats of Artisan Trade Topcoat with correct drying time between coats.

**Timber/Wood:** Apply one coat of Panache Wood Primer and wait 16-18 hours, followed by one coat of Artisan Trade Universal Undercoat and wait 16-18 hours, then apply two coats of your desired Artisan Trade Topcoat with correct drying time between coats.

**Gypsum Plaster (Rhinolite/Rhinoglide):** Apply one coat of Panache SB Plaster and wait 16-18 hours, followed by one coat of Artisan Trade Universal Undercoat, and wait 16 hours, followed by two coats of your desired Artisan Trade Topcoat with correct drying time between coats.

## PREVIOUSLY PAINTED SURFACES

Thoroughly clean and prepare surface by removing all dirt, grease, grime and flaking paint before painting. Powdery surfaces must be treated with one coat of Panache Bonding Liquid and wait 16-18 hours, prior to applying two coats of your desired Artisan Trade Topcoat with correct drying time between coats. Enamel based surfaces must be cleaned and prepared correctly. Sand lightly and apply one coat of Artisan Trade Universal Undercoat and wait 16-18 hours, followed by two coats of your desired Artisan Trade Topcoat with correct drying time between coats.

## APPLICATION

Stir the contents thoroughly before use. This product should be applied without thinning. For colour consistency, ensure that batch numbers are the same on all cans. Apply this product with a paintbrush or (mohair) paint roller and allow 16-18 hours drying time between coats. Do not apply when rain is imminent. Clean tools (brushes & rollers) with Mineral Turpentine immediately after use.

## COLOUR RANGE

Available in White

## PACKAGING:

Packaging: 5L, 20L

## SPREADING RATE

This product will cover approximately 6-8m<sup>2</sup> /litre, depending on surface porosity.

## TECHNICAL DATA

Type	Modified Alkyd
Finish	Matt
Drying Time @ 25°C	Touch Dry: 4-6 Hours Hard Dry: 16-18 Hours
Re-coating Time	16-18 Hours
Viscosity	80-85 Krebs units
Specific Gravity	-/+ 1.2 kg / Litre
Storage	Dry and Cool area

## PRECAUTIONS

- Do not apply if rain is imminent.
- Apply at an ambient temperature of 5 to 35°C.
- Keep out of reach of children.
- Wash hands with Mineral Turpentine immediately after use.
- Skin or Eye contact: clean with fresh water and consult a physician if necessary.
- Do not paint before 9:00 and after 15:30.

## TOOL CHECKLIST

Paintbrush & Paint Roller Tray Set; Plastic Drop Sheet; Mutton Cloth; Sandpaper; Masking Tape; Crack Filler; Paint Scraper; Stepladder and Mineral Turpentine.

## QUALITY GUARANTEE

This product is quality controlled and packed to the highest standard. Medal and Jack's Paint accepts no responsibility, nor accountability for either workmanship in surface preparation or the application of our products.

The information given in this Product Data Sheet is based on controlled laboratory tests and many years of experience. It is given in good faith, but no guarantee of any performance characteristic is given or implied. Jacks Paint cannot be held liable for consequential damage of whatsoever nature that may arise from the use of Panache products. Paint technology is continuously being developed and Jacks Paint reserves the right to update product specifications without prior notice. Contact Jacks Paint for further details on 0860 522 577.

