

Product Data Sheet



Steel Cladd Brick and Slasto Sealer

No	SC03
Date	07/21

Steel Cladd products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.

DESCRIPTION

Steel Cladd Brick and Slasto Sealer is an all-weather resistant finish coating, which is specifically designed to beautify, enhance, and protect interior and exterior brick or stonework. It can be used on a variety of surfaces such as face brick, stone, and quarry stone surfaces where a durable clear gloss finish is required.

PRODUCT USES

- Suitable for "Interior and Exterior" surfaces made from Brick & Stone.

PRODUCT BENEFITS

- Complete Protection
- Enhances the Natural Shades
- Easy to Clean & Maintain
- Dries to a Clear Gloss Finish
- Apply with Brush, Roller or Spray
- Interior & Exterior Use
- Quality Guaranteed

SURFACE PREPARATION

New Surfaces: Surface/s must be thoroughly clean, dry and in sound condition before varnishing. Apply one coat thinned down with 10% Mineral Turpentine followed by two coats (unthinned) of Steel Cladd Brick and Slasto Sealer to a clean and prepared surface.

Previously Sealed Surfaces: Thoroughly clean and prepare surface/s to be coated by removing all dirt, grease, grime, wax, oil and flaking varnish. The entire surface area must be properly cleaned with clean water and allowed to dry for 24 hours before commencing work. Apply one coat thinned down with 10% Mineral Turpentine followed by two coats of Steel Cladd Brick and Slasto Sealer.

Warning: This product is not suitable for use on Vinyl, or Ceramic Tiled floors, and must not be used on Damp surfaces.

APPLICATION

Stir the contents thoroughly before use. For colour consistency, ensure that batch numbers are

the same on all cans. Apply this product with a paintbrush, mohair roller or spray gun and allow overnight drying time between coats.

For Spray Application thin down with 15% Mineral Turpentine.

Clean tools (brushes & equipment) with Mineral Turpentine immediately after use.

COLOUR RANGE

Available in Clear.

SPREADING RATE

This product will cover approximately 8- 10 m² /litre, depending on surface porosity.

TECHNICAL DATA

Type	Alkyd
Finish	High Gloss
Drying Time @ 25°C	Touch Dry: 4 - 6 Hours Hard Dry: 16 - 18 Hours
Re-coating Time	16 - 18 Hours
Viscosity	60-65 KU
Specific Gravity	0.80 – 1.00kg / litre
Storage	Dry and Cool area
Pack Size	1Lt,5Lt

PRECAUTIONS

Do not apply if rain is imminent.

Apply at an ambient temperature lower than 35°C.

Keep out of reach of children.

Wash hands with Mineral Turpentine immediately after use and final wash with soap and water.

Skin or Eye contact: clean with fresh water and consult a physician if necessary.

TOOL CHECKLIST

Paintbrush; Plastic Drop Sheet; Mutton Cloth; Sandpaper; Masking Tape; Mineral Turpentine; Stepladder.

QUALITY GUARANTEE

This product is quality guaranteed to last under normal conditions, provided that the "Instructions for Use" appearing on the reverse side of each can have been correctly followed by the customer.

