

# Product Data Sheet



**Panache**  
PAINT

## Panache Artisan Roof Cote

No	JP20
Date	07/21

Panache Artisan products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.

### DESCRIPTION

Panache Artisan Roof Cote is a superior quality paint that provides long-life exterior durability combined with excellent alkali resistance. This product will provide complete protection against the harshest climatic conditions. It can be applied to Asbestos/Fibre Cement Tiles or Roof Sheets, Clay or Cement Roof Tiles and pre-primed Galvanised Iron Roofs.

### PRODUCT USES

- Suitable for most types of Roofing (exc. Slate).
- Concrete Windowsills.
- Primed Metal & Wooden Surfaces.
- Ideal for Exterior Surfaces.

### PRODUCT BENEFITS

- Excellent UV Resistance
- All-Weather Finish
- Excellent Hiding Power
- 8 Year Guarantee

### SURFACE PREPARATION

**New Surfaces:** Surface/s must be thoroughly clean, dry and in sound condition before painting.

**Concrete/Cement Plaster:** Apply one coat of Artisan Solvent Based Plaster Primer and wait 16 - 18 hours, then apply two coats of Artisan Satin Cote with correct drying time between coats.

**Asbestos/Fibre Cement:** Apply one coat of Artisan Solvent Based Plaster Primer and wait 16 - 18 hours, then apply two coats of Artisan Roof Cote with correct drying time between coats.

**Cement Roof Tiles/Nutec Tiles** – Apply one coat thinned down 10% to aid in adhesion. Then apply two coats of Artisan Roof Cote with correct drying time between coats.

**Galvanised Iron:** Apply one coat of Panache Anti-Corrosive Primer and wait 4-6 hours, then apply two coats of Artisan Roof Cote with correct drying time between coats.

**Iron & Steel:** Apply one coat of Panache Anti-Corrosive Primer and wait 4-6 hours, followed by one coat of Artisan Universal Undercoat and wait 16 - 18 hours, then apply two coats of Artisan Roof Cote with correct drying time between coats.

**Slate Roofs** – not recommended.

### PREVIOUSLY PAINTED SURFACES

Thoroughly clean and prepare surface by removing all dirt, grease, grime and flaking paint before painting. Powdery surfaces must be treated with one coat of Panache Bonding Liquid and wait 16 - 18 hours, prior to applying two coats of Artisan Roof Cote with correct drying time between coats.

Warning: Avoid painting if the roof is too hot or covered with mildew, which means that the recommended times may vary as indicated under Application

## APPLICATION

Stir the contents thoroughly before use. This product should be applied without thinning (except as directed for Cement and Nutec Tiles). For colour consistency, ensure that batch numbers are the same on all cans. For best results, apply this product between 08,00-11,00 hrs and again from 15,00-18,00 hrs. Apply this product with a paintbrush, block brush or (furpile / lambswool) paint roller, and allow +/- 4 hours drying time between coats. Allow paint to cure (hard dry) for 7 days before attempting to clean the surface. Do not apply when rain is imminent. Clean tools (brushes & rollers) with Water immediately after use.

## COLOUR RANGE

Available in Charcoal, Chrome Green, Clay Tile, Ebony, Red Oxide, Ruby, Slate Grey.

## PACKAGING

Packaging: 5L & 20L

## SPREADING RATE

This product will cover approximately 6-8m<sup>2</sup> /litre, depending on surface porosity.

## TECHNICAL DATA

Type	Acrylic
Finish	Sheen
Drying Time @ 25°C	Touch Dry: 1 - 2 Hour Hard Dry: 4 - 6 Hours
Re-coating Time	4 - 6 Hours
Viscosity	95-108 Krebs units
Specific Gravity	1.26 kg / Litre
Storage	Dry and Cool area

## PRECAUTIONS

Do not apply if rain is imminent.

Apply at an ambient temperature of 5 to 35°C.

Keep out of reach of children.

Wash hands with Water immediately after use.

Skin or Eye contact: clean with fresh water and consult a physician if necessary.

## TOOL CHECKLIST

Paintbrush & Paint Roller Tray set; Plastic Drop Sheet; Mutton Cloth; Sandpaper; Masking Tape; Crack filler; Paint Scraper; Stepladder.

## QUALITY GUARANTEE

This product is quality controlled and packed to the highest standard.

Medal and Jack's Paint accepts no responsibility, nor accountability for either workmanship in surface preparation or the application of our products.

The information given in this Product Data Sheet is based on controlled laboratory tests and many years of experience. It is given in good faith, but no guarantee of any performance characteristic is given or implied. Jacks Paint cannot be held liable for consequential damage of whatsoever nature that may arise from the use of Panache products. Paint technology is continuously being developed and Jacks Paint reserves the right to update product specifications without prior notice. Contact Jacks Paint for further details on 0860 522 577.

